



WHAT'S NEW:

Integrated slim foot for edge trimming Integrated welded counterblade New system for fuse replacement New PCB board with glass fuse Easy handling in 920 g only

FOLLOW US:







RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 • 20161 Milan · Italy ph. +39 02 66 22 12 31 • fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com



Blade diameter: 50 mm (1.96") with hard metal counterblade

Blade equipped: 50SEXTG, 7-edge 50 mm dia.

(1.96") EXTRA steel Blade speed: 1500 r.p.m.

Cutting ability: up to 8 mm (0.35")

Power: single phase – 55 W

Max. absorption: 1 A, with glass protection fuse **Net weight:** 920 g (with power supply cord) Total weight (with packing box): 1550 q **Electric cable length:** 1.5 mt (extensible)

Minimum brightness for working operations: LUX 200

Vibrations at start up: < 2.5 m/sec 2

Temperature range: 0 – 55 C

Umidity range: 10 - 95% without condensate









50SEXTG, 50 mm, 7-edges EXTRA GERMA-NY steel | **50SGHSS**, 50 mm, 7-edges HSS GERMANY steel | **50CHSS**, 50 mm, circular HSS steel | **50CK**, 50 mm, circular K190 steel **50SGHSSTF,** 50 mm, 7-edges HSS steel Teflon® coated.

