

1946

# SW100 ELECTRIC BENCH CUTTER

SW100. Flexibility and reliability since 30 years.



## **ELECTRIC BENCH CUTTER**

## **WHAT'S NEW:**

Low-friction Teflon® coated plate New double safety starting system New main power switch with Led

### **TECHNICAL DETAILS:**

Blade diameter: 100 mm (4"), with hard

metal counterblade

Blade equipped: 10EHSS, 6-edges, HSS steel

Blade speed: 850 r.p.m.

**Cutting ability:** up to 35 mm (1.4") Power: single phase - 90 W

Max. absorption: 2 A, with protection fuse **Net weight:** 2950 g (with power supply cord) Total weight (with packing box): 4550 q **Electric cable length:** 1.5 mt (with no plug)

Minimum brightness for working

operations: LUX 200

**Vibrations at start up:** < 2.5 m/sec 2

**Temperature range:**  $0 - 55 \, \text{C}$ **Umidity range:** 10 - 95% without

condensate









### **BLADES AVAILABLE:**

**10EHSS**, 100 mm 6-edges, HSS steel | **10SEXTG**, 100 mm 4-edges, EXTRA steel | **10CSW**, 100 mm circular, HSS steel | 10EHSSTF, 100 mm 6-edges, HSS steel Teflon® coated | 10EMD, 100 mm 6-edges, Carbide (Widia®)



### RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 20161 Milan · Italy ph. +39 02 66 22 12 31 fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com